

K4 SERIES



HIDROMEK





reddot winner 2023



GERMAN
DESIGN
AWARD
2023




K4 SERIES

HİDROMEK NEW K4 SERIES

The Newest and The Best Solution
For Your Work!

HİDROMEK's fourth generation backhoe loaders new K4 Series are your new assistants at your work with their perfect digging and loading performance.

K4 Series backhoe loaders drawing attention with their innovations and superior technology offer high performance with easy and safe usage and comfortable cabin in the fields and in the city.



Performance.....	6-7
Durability.....	8-9
Technology.....	10-15
Security.....	16-17
Opera.....	18
Comfort.....	19
HIDROMEKSmartlink.....	20-21
Ease of Service.....	22-23
Technical Features.....	24-28

The information and images, and equipment presented in this brochure are either standard or optional depending on the configuration. HIDROMEK has the right to modify the specifications and the designs of the model indicated in this brochure without prior notice.







Superior Performance

K4 Series backhoe loader offers versatile solutions with the advantage of being used for different works!

K4 Series enables you to work efficiently and productively thanks to its equipment. HMK 102B with its small front wheel and HMK 102S four-wheel equal models exceed your expectations offering the advantage of being used for many different works.

K4 Series, designed for severe geographical conditions and heavy working conditions, increases your productivity with its strong structure and efficient hydraulic system providing maximum breakout force even at lower revolutions and having high oil flow.

HIDROMEK K4 Series backhoe loaders facilitating works in excavation, infrastructure, superstructure, agriculture, forestry, landscaping and industrial areas thanks to their use with different attachments such as leveling shovel, forklift, hammer, auger, log, pendulum bucket, snow plow, scrap and paper collection bucket, bottom opening (big bag) bucket, stone collecting bucket, trapeze bucket, ripper and polyp attachment provide the benefits you expect.

20% Faster

K4 series backhoe loaders with accelerated movements through improved loader cylinder design do a lot of work in a short time during loading and unloading operations.

3% More Efficient

K4 Series backhoe loaders produce more work with less fuel as a result of the improvements made in cylinder design.



① Strong heavy - duty type steel construction



④ More durable front loader bucket reinforced with hardox



② Backhoe bucket form optimized and designed for better performance



⑤ Loader boom support device



③ Durable teeth structure



⑥ Durable engine front grille and protection bumper

Strong Steel Construction, Superior Durability!

K4 Series backhoe loaders, produced with advanced technology and advanced welding methods in HIDROMEK's modern production facilities, offer maximum performance, long life and trouble-free usage in tough field conditions with their strong steel construction. Powerful loader and excavator boom constructions and their arm and chassis are designed in accordance with severe conditions for long-term durability.





Power and Technology Together

Strong technological infrastructure of K4 Series ensures superior performance and fuel economy

Joystick Integrated Seats

Joysticks integrated to the seat enable the operator to work comfortably in backhoe and loader positions including the side angles.

Autotilt

In the cabin of K4 Series, which adjusts comfortably to the backhoe and loader positions, the Autotilt feature of the seat, patented by HIDROMEK, allows the steering wheel to lift up automatically while rotating back, and allows easy access to the backhoe position.

Shifter Button for Backhoe or Loader Function

Allows the operator to control backhoe or loader functions when needed without changing the direction of the seat.

* The Image indicates **ALPHA** model cabin interior.

④
Front Information Screen

①
Joystick Integrated Seats

Autotilt ②

③
Shifter Button for Backhoe or Loader Function



5 Rear Information Screen



Shifter Button for Backhoe or Loader Function



Autotilt



Shifter Button for Backhoe or Loader Function



Front Information Screen



Rear Information Screen

Screens

In the cabin, there are 2 different screens on the backhoe and loader sides. In Supra model, through rear screen controlled by HIDROMEK Opera, access to features such as speed adjustment according to the attachment type of the machine and periodic maintenance information screen is easily possible.



Front Information Screen

Joystick Integrated Seats

Autotilt

Shifter Button for Backhoe or Loader Function



5 Rear Information
Screen

* The Image indicates **SUPRA** model cabin interior.



⑥ Fully Automatic Transmission



⑦ Tipshift



⑧ Return-to-dig Function



⑨ Opera Control Button Integrated in the Seat (**)

Auto Idle (*)

Auto-Idle provides fuel saving by reducing idle automatically when the machine is working on backhoe side and be stationary for a certain period of time.

Load Sensing Hydraulic Pump (*)

FLOWSHARING featured valves offered together with piston pump allow simultaneous boom, arm and bucket movements even at low engine speeds regardless of load and user ability.

(*) This feature is optional depending on the package.



⑩ Tilting of the left joystick to some extent for the operator to work more comfortably on the loader side



Electronic Handbreak (**)



Hand Throttle with Electronic Rotary Control (*)



USB Socket



Automatic Control of Stabilizers (**)

LSD (Limited Slip Differential)

Thanks to LSD system, providing the most effective traction force on difficult grounds with the risk of skidding, tire changing periods of machine is extended while the work cycle times and fuel efficiency are significantly improved.

MSS (Motion Stabilizing System) (*)

Thanks to the MSS system, maximum productivity is achieved by preventing the fall of the load in the front bucket on rough terrain.

Automatic MSS (Motion Stabilizing System) (*)

Automatic MSS enables ease of use by being activated automatically at determined speeds.

(**) This feature is only available for **SUPRA** model.

Safe Working Environment!

- ROPS & FOPB cabin
- Wide view angle
- LED lighting (*)
- LED Beacon (*)
- Overload warning system (*)
- Boom and arm safety valves (*)
- Automatic Boom Lock activated after rotating to the loader side while working on the backhoe side. (*)
- For maintenance and access to the engine, boom lock integrated in loader arm cylinder
- Safety valves on the outriggers that can be used for safety while the machine is in stationary operation
- Mechanical driven rear excavator lock that ensures safe driving by keeping the rear boom of the machine stable during travel.
- Thanks to the braking system and emergency brake support even in extraordinary situations such as engine stalling, the machine comes to a safe stop with little pedal force.
- Immobilizer

(*) This feature is optional depending on the package.





OPERA, the guide of the field

K4 Series backhoe loaders are equipped with Opera (HiDROMEK Operator Interface) for the operator to use the machine easily, and feel comfortable and relaxed as he is in an office environment. Via Opera, which is controlled through the rear screen, operator can access many features easily.

- Speed adjustment through the back screen according to the type of the attachment.
- Bluetooth radio control (*)
- Language selection
- Data on operating hours and details
- Machine status information
- Maintenance time control through periodic maintenance screen
- Access to service page for authorized services
- Control of features such as volume, touch-tone and time through adjustment menu

Besides these features, in K4 Series:

- Control of breaker line valve from inside of the cabin (*)
- Adjustment of backhoe side from inside of the cabin through hydraulic table shifting system (*)
- Easy attachment changing through quick coupler
- Automatic fuel transfer pump (*)
- Additional installation which the hydraulic hand tools needed by the operator can be used with the help of machine hydraulic line (*)
- Compressor that provides instant elimination of pressure losses that may occur in tires (*)

(*) This feature is optional depending on the package.



Enjoyable and Comfortable Working in the Largest Volume Cabin in Its Class

- The largest volume cabin in its class which easily adapts to both the excavator and the loader positions
- Thanks to the joysticks on the seat, the operator is able to control the rear or front attachments, regardless of his position, and works comfortably including the side angles (*)
- Large back information display (*)
- Advanced air conditioning system (*)
- Compartment with cooling feature (*)
- Various storage compartments
- Cup Holders
- Phone holder
- USB charging
- Mechanical, air and heated seat types



(*) This feature is optional depending on the package.

You have the control with HiDROMEK **SmartLink**

Telematic system HiDROMEK Smartlink allows the user to easily access to machine location and technical information via computer and mobile phone.



To download Smartlink application

Follow the work time and location of your machine through HiDROMEK Smartlink!

Through GPS tracking system, it is possible to track the location and the work time intervals of the machine.



Follow the work time and location of your machine through HiDROMEK Smartlink!

Current and remaining fuel amount of the machine can be followed.



Check the works for which your machine has been used through HiDROMEK Smartlink!

During loading, digging and traveling operations, daily and total working hours and traction mode information can be seen.

Contact the nearest authorized service or regional service through HİDROMEK Smartlink!

With the application, it is possible to obtain the information on Regional and Authorized Services of HİDROMEK After Sales Services as well as the road directions to them.



Follow your machine's maintenance through HİDROMEK Smartlink!

Under the Alerts list, the machine's upcoming maintenance can be checked while the information of the nearest authorized service can be obtained, and it can be contacted.



Have performance reports for the selected periods of time for your machines through HİDROMEK Smartlink!

According to the date range, information can be determined such as daily working hours of the machine and in which locations it has worked can be obtained as a report.




Easy Maintenance and Service!

K4 Series, designed considering fast access to hydraulic and engine equipment, provide easy maintenance and service reducing service times and increasing machine downtime.

Service points where pump and transmission pressures are measured are located in easily accessible areas so that easy and fast maintenance is possible.

Openable Radiator Block For Quick and Safe Access

It offers easy maintenance and service by providing fast and safe access to hydraulic and engine equipment with its openable and easily cleanable radiator block and openable hood and right - left covers. In K4 Series, cleaning of the radiator is done more easily, the performance and health of the engine are always kept at a high level while efficient operation is provided.





HMK 102B - 102S

TECHNICAL FEATURES

ENGINE

Brand, Model	Perkins, 904J-E36TA
Number of cylinders	4
Max. Power	74,4 kW (100 HP) @2200 rpm
Max. Torque	430 Nm @1500 rpm
Displacement	3,621 cc
Bore & Stroke	ø 98 x 120 mm
Emission Class	EU:Stage 5, US: Tier 4 final

HYDRAULIC SYSTEM

System Type	Open Centre System	Close Centre System	
Pump Type	Gear Pump	Gear Pump	Piston Pump
Max. Flow @2200 rpm	Pump 1 90 L/min Pump 2 57,2 L/min	90 L/min 58 L/min	162 L/min
Main pump pressure	227 bar	255 bar	255 bar
Auxiliary pump pressure	170 bar	-	-

TIRES

	HMK 102B	HMK 102S
Front	16.70-20	16.9/14-28
Rear	16.9/14-28	16.9/14-28

AXLES

	HMK 102B	HMK 102S
Front Axle	Torque proposal	Torque proposal
Rear Axle	Limited slip (LSD) Differential lock (Option)	Differential lock

DRIVING SPEED

1 st gear	4	km/h
2 nd gear	7	km/h
3 rd gear	9	km/h
4 th gear	15	km/h
5 th gear	22	km/h
6 th gear	40	km/h

BRAKES

Service Brake	Self adjusting, multi disc oil bath type, hydraulic actuated brakes are located in the rear axle and act on 4 wheels
Parking Brake	Hand lever operated mechanical brake acts on the rear axle differential Button operated electrical brake acts on the rear axle differential (SUPRA)

TRANSMISSION

Autoshift transmission for heavy duty service
Torque converter with 2,38:1 stall ratio
Electrically controlled 2 Wheel drive or 4 Wheel Drive selection
6 forward, 3 reverse gears (Lock-Up is option)
Transmission oil cooler
A neutral circuit allows starting only when the control lever is in neutral position for safety.

FILLING CAPACITIES

	HMK 102B	HMK 102S
Engine oil pump	10 L	10 L
Engine cooling system	16 L	16 L
Fuel Tank	140 L	140 L
Hydarulic oil tank	70 L	70 L
Transmission oil	16 L	16 L
Ad Blue	19 L	19 L

LOADER PERFORMANCE

6 in 1 bucket capacity	11 m ³
Max. bucket breakout force	7380 kgf
Max. loading arm breakout force	7380 kgf
Lifting capacity to max. height	3360 kg

BACKHOE PERFORMANCE


	Standard arm	Telescopic arm extended	Telescopic arm retracted
Bucket capacity		0.18 m ³	
Max. bucket breakout force	6865 kgf	7020 kgf	7020 kgf
Max. arm breakout force	3290 kgf	2230 kgf	3160 kgf

ELECTRICAL SYSTEM

Voltage	12 V	Starter Motor	4 Kw
Battery	140 A	Alternator	120 A

OPERATING WEIGHT

	HMK 102B	HMK 102S
Operating weight with standard equipment	9300 kg	9650 kg



DIMENSIONS (mm)

		102B		102S	
		TB (extended)	TB (retracted)	TB (extended)	TB (retracted)
A	Maximum digging depth	5606	4484	5610	4362
B	Ground level to rear wheel centre	8188	7070	8237	7007
C	Ground level to slew centre	6819	5691	6834	5759
D	Loading distance	3150	2278	3150	2173
E	Distance to machine central line	7423	6282	7432	6173
F	Operating height	6589	5667	6560	5635
G	Max. loader height	5598	4705	4651	4651
H	Total kingpost travel	1141		1140	
J	Bucket rotation (°)	187		187	
K	Shovel Width	2422		2420	
L	Rear frame width	2270		2267	
M	Dump height	2596		2671	
N	Load over height	3295		3365	
O	Pin height	3445		3515	
P	Front arm pin - bumper distance	542		415	
Q	Grab lug - bumper distance	1492		1410	
R	Max. reach at full height	1491		1371	
S	Unloading distance	1005		889	
T	Digging depth	185		110	
U	Roll back at ground (°)	43		43	
V	Dump angle (°)	47,3		47,5	
Y	Front wheel centre to the ground	490		680	
Z	Departure angle (°)	22		23,3	
W	Rear wheel centre to ground	650		630	
X	Distance between pin centre and ground	250		250	
AA	Total travel length	6017		6088	
BB	Axle centreline distance	2219		2272	
CC	Slew centre to rear axle centre distance	1339		1403	
DD	Stabilizer feet clearance	323		350	
EE	Kingpost clearance	467		490	
FF	Steering wheel centre height	2043		2122	
GG	Cab roof height	2860		2887	
HH	Total travel clearance	3604		3513	


HMK 102B - 102S

EQUIPMENT


ENGINE / TRANSMISSION	ALPHA	SUPRA
Water cooled, turbo diesel engine	●	●
Foldable cooling pack	●	●
Full view engine pre cleaner filter	●	0
Turbo type engine pre cleaner filter	0	●
Engine glow plug	●	●
6 forward automatic transmission	●	●
Transmission oil cooler	●	●
Lock up	0	●
Auto throttle	●	●
Auto stop	●	●
Automatic reversible fan	0	0
CAB	ALPHA	SUPRA
Joystick control	0	●
Phone holder	●	●
USB charging port	●	●
LED interior lights	●	●
4.3" front display	●	●
7" rear side display	-	●
Auto tilt steering wheel	●	●
Pool type floor mat	●	●
Cooling box	0	●
Tipshift /FNR	●	●
RTD (Return to dig)	●	●
Multi purpose bucket proposal control	●	●
Floating	●	●
Air conditioner	0	●
Roof rack	●	●
MP3 radio	●	●
Bluetooth radio	0	0
Side steps lights	-	●
Air suspension seat	0	●
Interior rearview mirror	0	0
SECURITY	ALPHA	SUPRA
FOPS/ROPS	●	●
Electronic park brake	-	●
Loader boom lock	●	●
Hydraulic backhoe boom	-	●
Immobilizer	●	●
Halogen working lights	●	-
LED working lights	-	●
Side working lights	-	●
Auto boom lock	-	●
Reverse camera	0	0
Halogen cab light	●	-
LED cab light	0	●
Multimod cab light	0	0
Over load warning system	0	0
Double brake system	●	●
Emergency brake system	●	●
Fire extinguisher	0	0
Cab protective Group	0	0

AXLES	HMK 102B	HMK 102S
Tork proposal type, front	●	●
Limited sleep (LSD) type, rear	●	0
Differential lock	0	●
TYRES	ALPHA	SUPRA
16.70-20 (HMK 102B)	●	●
16.9/14-28 (HMK 102S)	●	●
14.5-20 (HMK 102B)	0	0
16.9-R28 Radial (HMK 102S)	0	0
HYDRAULIC SYSTEM	ALPHA	SUPRA
Bi-directional working	0	●
Proposal stabilisers control	-	●
Automatic stabilisers control system	-	●
MSS (Motion Stabilizer System)	0	●
Auto MSS	0	●
Mechanical Cross Control Lever	0	-
SAE / ISO control type	0	●
Cylinders with Cushion	●	●
Hose Burst Valve (Stabiliser Cylinder)	0	0
Hose Burst Valve (Backhoe arm cylinder)	0	0
Hose Burst Valve (Loader arm cylinder)	●	●
Unloader	●	●
Service Point for transmission and hydraulic pressure measurement	●	●
Piston pump	0	●
Extendable Arm	0	●
Extendable Narrow Arm	0	0
Articulated Boom	0	0
Wing type stabiliser	0	0
Hydraulic quick coupler	0	0
Single line breakeer line	●	●
Double acting line	0	0
Double acting additional line	0	0
Power slider	0	0
OTHERS	ALPHA	SUPRA
Smartlink	0	●
Fuel transfer pump	0	0
Working lights cover	0	0
Tunnel application (Breaker line filter, bucket cylinder protection, boom stopper)	0	0
Single acting / double acting line selection from inside the cabin (with extendable arm)	0	0
Electrical breaker line valve (with standard arm)	0	0
Double acting additional line selecting at cab	0	0
Air compressor	0	0
Hand breaker line	0	0
Tool kit	●	●


● STANDARD 0 OPTIONAL




Multi purpose bucket options




General purpose bucket




Fork for multi purpose bucket




Fork arms, for quick couple mechanism



Single axial levelling blade




2 axial levelling blade



Snow blade



Fork arms with quick coupler



Big bag bucket



2+1 Log grapple




3+2 Log grapple



Timber grab




Adapter for log grapples




Scrap collecting bucket




Paper collecting bucket



Tilting bucket



Quick coupler for loader side



Mechanical quick coupler



Hydraulic quick coupler



Hydraulic breaker



Auger



Tilting bucket




Backhoe bucket of different sizes




Polip




Ripper



Trapezoidal ditch bucket



Excavator thump attachment




Tilting bucket for backhoe



Dry log splitter



Ditch cleaning bucket (1500 mm)



Towing hook



Notes

HIDROMEK®

HEAD OFFICE

Address : Ahi Evran OSB Mahallesi,
Osmanlı Caddesi, No:1, 06935
Sincan-ANKARA/TÜRKİYE

Phone : +90 312 267 12 60

Fax : +90 312 267 12 39

E-mail: export@hidromek.com.tr

AFTER SALES SERVICE

Address : İstanbul Yolu 17. Km,
Şehit Osman Avcı Mahallesi,
No: 479, Etimesgut-ANKARA/TÜRKİYE

Phone : +90 312 280 87 40

Fax : +90 312 280 87 48

HIDROMEK® WEST

HIDROMEK MAQUINARIA DE CONSTRUCCION ESPAÑA S.L.

Address : Avenida Del Progres 7 08840 –
Viladecans Barcelona/ SPAIN

Phone : +34 93 638 84 65

E-mail : info@hidromek.es

HIDROMEK® JAPAN

Address : 5-10, Hashimoto 6-chome,
Midori-Ku, Sagamihara,
Kanagawa, 252-0143 JAPAN

Phone : +81 42 703 0261

Fax : +81 42 703 0262

E-mail : Kiyoko.Shinoda@hidromek.com

HIDROMEK® RUS

Address : 72, Zhivopisnaya str., Building A,
village Oktyabrskiy,
Krasnodar, 350032, RUSSIA

Phone : +7 861 290 3007

E-mail : hidromekrus@hidromek.ru


HIDROMEK® HCE

HIDROMEK Construction Equipment (Thailand) Ltd.

Address : Amata City Chonburi Industrial Estate Phase 7,
No. 700/669 Moo 1, T.Phanthong,
A.Phanthong, Chonburi 20160, TAYLAND

Phone : +66 38 447 349

Fax : +66 38 447 355



- HíDROMEK Production Facilities
- HíDROMEK Overseas Dealers
- ▼ HíDROMEK Overseas Sales and Aftersales Services Points
- Countries HíDROMEK Machines Running

HIDROMEK®

Together Stronger

www.hidromek.com

[f hidromek.tr](https://www.facebook.com/hidromek.tr) [X Hidromek](https://x.com/Hidromek) [ig hidromekofficial](https://www.instagram.com/hidromekofficial) [HydromekTv](https://www.youtube.com/HidromekTv) [in company/hidromek](https://www.linkedin.com/company/hidromek)

ENG - MARCH 2024 / 010324 - V

